



## SAFETY DATA SHEET ProTect ST

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name ProTect ST

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses PC 9a: Coatings and paints, thinners, paint removers. Paint coating for industrial application on metal surfaces.

Uses advised against For professional users only.

#### 1.3. Details of the supplier of the safety data sheet

Supplier Axalta Coating Systems Huthwaite UK Ltd  
Blackwell Road  
Huthwaite  
Nottinghamshire  
United Kingdom  
NG17 2RL  
Tel: +44 (0)1623 510585

Contact person info-huthwaite@axaltacs.com

#### 1.4. Emergency telephone number

Emergency telephone United Kingdom: 01623 528938 (Mon-Thu 0700 - 1600 hrs, Fri 0700 - 1245 hrs).

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification (EC 1272/2008)

Physical hazards Flam. Liq. 3 - H226

Health hazards Skin Irrit. 2 - H315 Eye Dam. 1 - H318 Skin Sens. 1 - H317

Environmental hazards Aquatic Chronic 2 - H411

#### 2.2. Label elements

##### Hazard pictograms



Signal word

Danger

Hazard statements

H226 Flammable liquid and vapour.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H318 Causes serious eye damage.  
H411 Toxic to aquatic life with long lasting effects.

## ProTect ST

<b>Precautionary statements</b>	<p>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</p> <p>P261 Avoid breathing vapour/ spray.</p> <p>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.</p> <p>P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P403+P235 Store in a well-ventilated place. Keep cool.</p> <p>P501 Dispose of contents/ container in accordance with national regulations.</p>
<b>Contains</b>	EPOXY RESIN (Number average MW ≤ 700 ), ISO-BUTANOL, NONYLPHENOL
<b>Supplementary precautionary statements</b>	<p>P233 Keep container tightly closed.</p> <p>P240 Ground and bond container and receiving equipment.</p> <p>P241 Use explosion-proof electrical equipment.</p> <p>P242 Use non-sparking tools.</p> <p>P243 Take action to prevent static discharges.</p> <p>P264 Wash contaminated skin thoroughly after handling.</p> <p>P272 Contaminated work clothing should not be allowed out of the workplace.</p> <p>P273 Avoid release to the environment.</p> <p>P302+P352 IF ON SKIN: Wash with plenty of water.</p> <p>P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.</p> <p>P310 Immediately call a POISON CENTER/ doctor.</p> <p>P321 Specific treatment (see medical advice on this label).</p> <p>P332+P313 If skin irritation occurs: Get medical advice/ attention.</p> <p>P333+P313 If skin irritation or rash occurs: Get medical advice/ attention.</p> <p>P362+P364 Take off contaminated clothing and wash it before reuse.</p> <p>P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.</p> <p>P391 Collect spillage.</p>

### Other information

#### 2.3. Other hazards

#### SECTION 3: Composition/information on ingredients

##### 3.2. Mixtures

<b>4,4'-ISOPROPYLIDENEDIPHENOL, OLIGOMERIC</b>		<b>10-30%</b>
<b>REACTION PRODUCTS WITH 1-CHLORO-2,3-EPOXYPROPANE</b>		
CAS number: 25068-38-6	EC number: 500-033-5	REACH registration number: 01-2119456619-26-XXXX
<b>Classification</b>		
Skin Irrit. 2 - H315		
Eye Irrit. 2 - H319		
Skin Sens. 1 - H317		
Aquatic Chronic 2 - H411		

## ProTect ST

<b>XYLENE</b>		<b>5-10%</b>
CAS number: 1330-20-7	EC number: 215-535-7	REACH registration number: 01-2119488216-32-0000
<b>Classification</b>		
Flam. Liq. 3 - H226 Acute Tox. 4 - H312 Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Asp. Tox. 1 - H304		
<b>ISO-BUTANOL</b>		<b>1-5%</b>
CAS number: 78-83-1	EC number: 201-148-0	REACH registration number: 01-2119484609-23-0000
<b>Classification</b>		
Flam. Liq. 3 - H226 Skin Irrit. 2 - H315 Eye Dam. 1 - H318 STOT SE 3 - H335, H336		
<b>NAPHTHA (PETROLEUM), HYDROTREATED HEAVY</b>		<b>1-5%</b>
CAS number: 64742-48-9	EC number: 265-150-3	REACH registration number: 01-2119486659-16-0000
<b>Classification</b>		
Flam. Liq. 3 - H226 STOT SE 3 - H336 Asp. Tox. 1 - H304		
<b>NONYLPHENOL</b>		<b>1-5%</b>
CAS number: 25154-52-3	EC number: 246-672-0	
M factor (Acute) = 1	M factor (Chronic) = 1	
<b>Classification</b>		
Acute Tox. 4 - H302 Skin Corr. 1B - H314 Eye Dam. 1 - H318 Repr. 2 - H361fd Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410		

## ProTect ST

<b>ETHYLBENZENE</b> <span style="float: right;"><b>&lt;1%</b></span>
<div style="display: flex; justify-content: space-between;"> <span>CAS number: 100-41-4</span> <span>EC number: 202-849-4</span> <span>REACH registration number: 01-2119489370-35-0000</span> </div>
<b>Classification</b> Flam. Liq. 2 - H225 Acute Tox. 4 - H332 STOT RE 2 - H373 Asp. Tox. 1 - H304
<b>CYCLOHEXANONE</b> <span style="float: right;"><b>&lt;1%</b></span>
<div style="display: flex; justify-content: space-between;"> <span>CAS number: 108-94-1</span> <span>EC number: 203-631-1</span> <span>REACH registration number: 01-2119453616-35-0000</span> </div>
<b>Classification</b> Flam. Liq. 3 - H226 Acute Tox. 4 - H332
<b>CUMENE</b> <span style="float: right;"><b>&lt;1%</b></span>
<div style="display: flex; justify-content: space-between;"> <span>CAS number: 98-82-8</span> <span>EC number: 202-704-5</span> <span>REACH registration number: 01-2119473983-24-0000</span> </div>
<b>Classification</b> Flam. Liq. 3 - H226 STOT SE 3 - H335 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411
<b>2-METHOXY-1-METHYLETHYL ACETATE</b> <span style="float: right;"><b>&lt;1%</b></span>
<div style="display: flex; justify-content: space-between;"> <span>CAS number: 108-65-6</span> <span>EC number: 203-603-9</span> <span>REACH registration number: 01-2119475791-29-0000</span> </div>
<b>Classification</b> Flam. Liq. 3 - H226 STOT SE 3 - H336

The full text for all hazard statements is displayed in Section 16.

**Composition comments**      The data shown are in accordance with the latest EC Directives.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

<b>General information</b>	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Never give anything by mouth to an unconscious person. Get medical attention if any discomfort continues.
<b>Inhalation</b>	Place unconscious person on their side in the recovery position and ensure breathing can take place. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Get medical attention if any discomfort continues.

## ProTect ST

<b>Ingestion</b>	Rinse mouth thoroughly with water. Give plenty of water to drink. Give milk instead of water if readily available. Keep affected person under observation. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention immediately. Show this Safety Data Sheet to the medical personnel.
<b>Skin contact</b>	Remove contaminated clothing immediately and wash skin with soap and water. Get medical attention if symptoms are severe or persist after washing.
<b>Eye contact</b>	Remove any contact lenses and open eyelids wide apart. Rinse immediately with plenty of water. Continue to rinse for at least 15 minutes. Get medical attention promptly if symptoms occur after washing.

### 4.2. Most important symptoms and effects, both acute and delayed

**General information** No data available on the mixture itself.

### 4.3. Indication of any immediate medical attention and special treatment needed

**Notes for the doctor** Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

**Suitable extinguishing media** Extinguish with the following media: Water spray, fog or mist. Foam, carbon dioxide or dry powder. Dry chemicals, sand, dolomite etc.

### 5.2. Special hazards arising from the substance or mixture

**Specific hazards** The product is flammable. Heating may generate flammable vapours.

**Hazardous combustion products** Thermal decomposition or combustion products may include the following substances: Toxic gases or vapours.

### 5.3. Advice for firefighters

**Protective actions during firefighting** Move containers from fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. Control run-off water by containing and keeping it out of sewers and watercourses.

**Special protective equipment for firefighters** Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions** Wear protective clothing as described in Section 8 of this safety data sheet.

**For non-emergency personnel** Keep unnecessary and unprotected personnel away from the area.

### 6.2. Environmental precautions

**Environmental precautions** Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body.

### 6.3. Methods and material for containment and cleaning up

**Methods for cleaning up** Keep combustible materials away from spillage. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Absorb in vermiculite, dry sand or earth and place into containers. Wash thoroughly after dealing with a spillage.

### 6.4. Reference to other sections

**Reference to other sections** For personal protection, see Section 8. For waste disposal, see Section 13.

## ProTect ST

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

**Usage precautions** Keep away from heat, sparks and open flame. Avoid spilling. Avoid contact with skin and eyes. Provide adequate ventilation. Avoid inhalation of vapours. Use approved respirator if air contamination is above an acceptable level.

#### 7.2. Conditions for safe storage, including any incompatibilities

**Storage precautions** Keep away from oxidising materials, heat and flames. Store in tightly-closed, original container in a dry, cool and well-ventilated place. Avoid contact with oxidising agents.

**Storage class** Flammable liquid storage.

#### 7.3. Specific end use(s)

**Specific end use(s)** The identified uses for this product are detailed in Section 1.2.

### SECTION 8: Exposure controls/Personal protection

#### 8.1. Control parameters

##### Occupational exposure limits

##### XYLENE

Long-term exposure limit (8-hour TWA): WEL 50 ppm(Sk) 220 mg/m<sup>3</sup>(Sk)

Short-term exposure limit (15-minute): WEL 100 ppm(Sk) 441 mg/m<sup>3</sup>(Sk)

Occupational Exposure Limits (Ireland):

Long-term exposure limit (8-hour TWA): NAOSH (Ireland) OELV 8 hours; 50 ppm 221 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): NAOSH (Ireland) OELV-15 min 100 ppm 442 mg/m<sup>3</sup>

##### ISO-BUTANOL

Long-term exposure limit (8-hour TWA): WEL 50 ppm 154 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 75 ppm 231 mg/m<sup>3</sup>

Long-term exposure limit (8-hour TWA): NAOSH (Ireland) OELV 8 hours; 50 ppm 150 mg/m<sup>3</sup>

Long-term exposure limit (8-hour TWA): NAOSH (Ireland) OELV-15 min 75 ppm 225 mg/m<sup>3</sup>

##### NAPHTHA (PETROLEUM), HYDROTREATED HEAVY

Long-term exposure limit (8-hour TWA): WEL 1000 mg/m<sup>3</sup>

##### ETHYLBENZENE

Long-term exposure limit (8-hour TWA): WEL 100 ppm 441 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 125 ppm 552 mg/m<sup>3</sup>

Sk

Occupational Exposure Limits (Ireland):

Long-term exposure limit (8-hour TWA): NAOSH (Ireland) OELV 8 hours; 100 ppm 442 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): NAOSH (Ireland) OELV-15 min 200 ppm 884 mg/m<sup>3</sup>

##### CYCLOHEXANONE

Long-term exposure limit (8-hour TWA): WEL 10 ppm(Sk)

Short-term exposure limit (15-minute): WEL 20 ppm(Sk)

##### CUMENE

Long-term exposure limit (8-hour TWA): WEL 25 ppm(Sk) 125 mg/m<sup>3</sup>(Sk)

Short-term exposure limit (15-minute): WEL 50 ppm(Sk) 250 mg/m<sup>3</sup>(Sk)

##### 2-METHOXY-1-METHYLETHYL ACETATE

Long-term exposure limit (8-hour TWA): WEL 50 ppm(Sk) 274 mg/m<sup>3</sup>(Sk)

Short-term exposure limit (15-minute): WEL 100 ppm(Sk) 548 mg/m<sup>3</sup>(Sk)

Occupational Exposure Limits (Ireland):

Long-term exposure limit (8-hour TWA): NAOSH (Ireland) OELV 8 hours; 50 ppm 275 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): NAOSH (Ireland) OELV-15 min 100 ppm 550 mg/m<sup>3</sup>

## ProTect ST

WEL = Workplace Exposure Limit  
Sk = Can be absorbed through the skin.

**Ingredient comments** WEL = Workplace Exposure Limits

### 4,4'-ISOPROPYLIDENEDIPHENOL, OLIGOMERIC REACTION PRODUCTS WITH 1-CHLORO-2,3-EPOXYPROPANE (CAS: 25068-38-6)

<b>DNEL</b>	<p>Industry - Dermal; Short term systemic effects: 8.33 mg/kg/day          Industry - Inhalation; Short term systemic effects: 12.25 mg/m<sup>3</sup>          Industry - Dermal; Long term systemic effects: 8.33 mg/kg/day          Industry - Inhalation; Long term systemic effects: 12.25 mg/m<sup>3</sup>          Consumer - Dermal; Short term systemic effects: 3.571 mg/kg/day          Consumer - Oral; Short term systemic effects: 0.75 mg/kg/day          Consumer - Dermal; Long term systemic effects: 3.571 mg/kg/day          Consumer - Oral; Long term systemic effects: 0.75 mg/kg/day</p>
<b>PNEC</b>	<p>Fresh water; 0.006 mg/l          marine water; 0.0006 mg/l          Intermittent release; 0.018 mg/l          STP; 10 mg/l          Sediment (Freshwater); 0.996 mg/l          Sediment (Marinewater); 0.0996 mg/l          Soil; 0.196 mg/kg</p>

### NAPHTHA (PETROLEUM), HYDROTREATED HEAVY (CAS: 64742-48-9)

<b>DNEL</b>	<p>Workers - Dermal; Long term systemic effects: 208 mg/kg          Workers - Inhalation; Long term systemic effects: 871 mg/m<sup>3</sup>          General population - Dermal; Long term systemic effects: 125 mg/kg          General population - Inhalation; Long term systemic effects: 185 mg/m<sup>3</sup>          General population - Oral; Long term systemic effects: 125 mg/kg</p>
-------------	---

### HYDROCARBONS, C9-C11, n-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS

<b>DNEL</b>	<p>Industry - Dermal; Long term systemic effects: 208 mg/kg/day          Industry - Inhalation; Long term systemic effects: 871 mg/m<sup>3</sup>          Consumer - Dermal; Long term systemic effects: 125 mg/kg/day          Consumer - Inhalation; Long term systemic effects: 185 mg/m<sup>3</sup>          Consumer - Oral; Long term systemic effects: 125 mg/kg/day</p>
-------------	---

## 8.2. Exposure controls

### Protective equipment



### Appropriate engineering controls

Provide adequate general and local exhaust ventilation. Observe any occupational exposure limits for the product or ingredients. All handling should only take place in well-ventilated areas.

### Eye/face protection

Wear chemical splash goggles. Personal protective equipment for eye and face protection should comply with European Standard EN166.

## ProTect ST

<b>Hand protection</b>	Wear protective gloves. To protect hands from chemicals, gloves should comply with European Standard EN374. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. Gloves made from the following material may provide suitable chemical protection: Butyl Rubber; thickness 0.5mm minimum. PVC; thickness 0.5mm minimum. Viton rubber (fluoro rubber). Neoprene. Glove thickness is not necessarily a good measure of glove resistance as the permeation rate will depend on the exact glove composition. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected.
<b>Other skin and body protection</b>	Wear appropriate clothing to prevent any possibility of skin contact.
<b>Hygiene measures</b>	Provide eyewash station. Do not smoke in work area. Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.
<b>Respiratory protection</b>	Wear a respirator fitted with the following cartridge: Organic vapour filter.

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

<b>Appearance</b>	Viscous liquid.
<b>Colour</b>	Silver.
<b>Odour</b>	Characteristic.
<b>Initial boiling point and range</b>	108°C
<b>Flash point</b>	25°C Closed cup.
<b>Upper/lower flammability or explosive limits</b>	Lower flammable/explosive limit: 0.7% Upper flammable/explosive limit: 10.9%
<b>Vapour pressure</b>	Not available.
<b>Relative density</b>	1.42 - 1.44
<b>Solubility(ies)</b>	Immiscible with water.
<b>Partition coefficient</b>	Not available.
<b>Viscosity</b>	Kinematic viscosity > 20.5 mm <sup>2</sup> /s.

#### 9.2. Other information

<b>Other information</b>	No additional information
<b>Volatile organic compound</b>	This product contains a maximum VOC content of 228 g/l.

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

<b>Reactivity</b>	See the other subsections of this section for further details.
-------------------	--

#### 10.2. Chemical stability

<b>Stability</b>	No particular stability concerns.
------------------	-----------------------------------

#### 10.3. Possibility of hazardous reactions

<b>Possibility of hazardous reactions</b>	Under normal conditions of storage and use, no hazardous reactions will occur.
---	--

## ProTect ST

### 10.4. Conditions to avoid

**Conditions to avoid** Avoid heat, flames and other sources of ignition.

### 10.5. Incompatible materials

**Materials to avoid** Avoid contact with the following materials: Strong oxidising agents.

### 10.6. Hazardous decomposition products

**Hazardous decomposition products** Oxides of carbon.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### Acute toxicity - oral

**ATE oral (mg/kg)** 43,290.04

#### Acute toxicity - dermal

**ATE dermal (mg/kg)** 18,818.86

#### Acute toxicity - inhalation

**ATE inhalation (gases ppm)** 76,986.25

**ATE inhalation (vapours mg/l)** 188.19

**ATE inhalation (dusts/mists mg/l)** 25.66

**General information** Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.

**Inhalation** Gas or vapour in high concentrations may irritate the respiratory system. Symptoms following overexposure may include the following: Coughing.

**Ingestion** Gastrointestinal symptoms, including upset stomach.

**Skin contact** Product has a defatting effect on skin. May cause allergic contact eczema. Irritating to skin. May cause sensitisation by skin contact.

**Eye contact** Irritating to eyes.

## SECTION 12: Ecological information

**Ecotoxicity** Toxic to aquatic life with long lasting effects.

### 12.1. Toxicity

**Toxicity** No data on the mixture itself.

### 12.2. Persistence and degradability

**Persistence and degradability** No data available.

### 12.3. Bioaccumulative potential

**Bioaccumulative potential** No data available on bioaccumulation.

**Partition coefficient** Not available.

### 12.4. Mobility in soil

**Mobility** No data available.

## ProTect ST

### 12.5. Results of PBT and vPvB assessment

**Results of PBT and vPvB assessment** No data available.

### 12.6. Other adverse effects

**Other adverse effects** None known.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

**General information** Waste should be treated as controlled waste.

**Disposal methods** Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Containers should be thoroughly emptied before disposal because of the risk of an explosion. Absorb in vermiculite, dry sand or earth and place into containers. Dispose of waste via a licensed waste disposal contractor.

## SECTION 14: Transport information

### 14.1. UN number

UN No. (ADR/RID)	1263
UN No. (IMDG)	1263
UN No. (ICAO)	1263
UN No. (ADN)	1263

### 14.2. UN proper shipping name

Proper shipping name (ADR/RID)	PAINT
Proper shipping name (IMDG)	PAINT
Proper shipping name (ICAO)	PAINT
Proper shipping name (ADN)	PAINT

### 14.3. Transport hazard class(es)

ADR/RID class	3
ADR/RID classification code	F1
ADR/RID label	3
IMDG class	3
ICAO class/division	3
ADN class	3

### Transport labels



### 14.4. Packing group

ADR/RID packing group	III
IMDG packing group	III

## ProTect ST

ICAO packing group III

ADN packing group III

### 14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



### 14.6. Special precautions for user

EmS F-E, S-E

ADR transport category 3

Emergency Action Code •3Y

Hazard Identification Number (ADR/RID) 30

Tunnel restriction code (D/E)

### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**EU legislation** Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).  
Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

**Guidance** Workplace Exposure Limits EH40.

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

## SECTION 16: Other information

**Abbreviations and acronyms used in the safety data sheet** WEL: Workplace Exposure Limit.  
ATE: Acute Toxicity Estimate.  
CAS: Chemical Abstracts Service.  
DMEL: Derived Minimal Effect Level.  
DNEL: Derived No Effect Level.  
PNEC: Predicted No Effect Concentration.  
PBT: Persistent, Bioaccumulative and Toxic substance.  
vPvB: Very Persistent and Very Bioaccumulative.

**Revision date** 14/08/2018

**Revision** 3

**Supersedes date** 15/02/2018

## ProTect ST

<b>SDS number</b>	17400
<b>Hazard statements in full</b>	H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour. H302 Harmful if swallowed. H304 May be fatal if swallowed and enters airways. H312 Harmful in contact with skin. H314 Causes severe skin burns and eye damage. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H319 Causes serious eye irritation. H332 Harmful if inhaled. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H361fd Suspected of damaging fertility. Suspected of damaging the unborn child. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects.

The information in this SDS is based on the present state of our knowledge and meets the requirements of EU and national laws. The user's working conditions however, are beyond our knowledge and control. The product is not to be used for purposes other than those specified under section 1 without a written permission. It remains the responsibility of the user to ensure that the necessary steps are taken to meet the laws and regulations. Handling of the product may only be done by people above 18 years of age, who are satisfactorily informed of how to do the work, the hazardous properties and necessary safety precautions. The information given in this SDS is to describe the product only in terms of health and safety requirements and should not, therefore, be construed as guaranteeing specific properties.



## SAFETY DATA SHEET

### ProTect ST and Protect STC curing agent

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

##### 1.1. Product identifier

**Product name P** ProTect ST and Protect STC curing agent

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** PC 9a: Coatings and paints, thinners, paint removers. Curing agent for use in two pack epoxy coatings.

**Uses advised against** For professional users only.

##### 1.3. Details of the supplier of the safety data sheet

**Supplier** Protective Polymers Ltd  
Lydford Road  
Meadow Lane Industrial Estate  
Alfreton  
DE55 7RQ

**Contact person** SDS@protectivepolymers.com

##### 1.4. Emergency telephone number

**Emergency telephone** +44 (0)1623 441106(Not 24 Hours)

#### SECTION 2: Hazards identification

##### 2.1. Classification of the substance or mixture

###### Classification (EC 1272/2008)

**Physical hazards** Flam. Liq. 3 - H226

**Health hazards** Acute Tox. 4 - H302 Acute Tox. 4 - H332 Skin Corr. 1B - H314 Eye Dam. 1 - H318 Skin Sens. 1 - H317

**Environmental hazards** Not Classified

##### 2.2. Label elements

###### Hazard pictograms



**Signal word**

Danger

###### Hazard statements

H226 Flammable liquid and vapour.  
H302+H332 Harmful if swallowed or if inhaled.  
H314 Causes severe skin burns and eye damage.  
H317 May cause an allergic skin reaction.

## ProTect ST and Protect STC curing agent

<b>Precautionary statements</b>	<p>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</p> <p>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.</p> <p>P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.</p> <p>P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P403+P235 Store in a well-ventilated place. Keep cool.</p> <p>P405 Store locked up.</p> <p>P501 Dispose of contents/ container in accordance with national regulations.</p> <p>P260 Do not breathe vapour/ spray.</p> <p>P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.</p> <p>P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.</p>
---------------------------------	---

**Contains** BENZYL ALCOHOL, ISOPHORONEDIAMINE, TRIETHYLENETETRAMINE, XYLENE

### Other information

#### 2.3. Other hazards

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

<p><b>BENZYL ALCOHOL</b> <span style="float: right;"><b>30-60%</b></span></p> <p>CAS number: 100-51-6                      EC number: 202-859-9                      REACH registration number: 01-2119492630-38-0000</p>
<p><b>Classification</b></p> <p>Acute Tox. 4 - H302 Acute Tox. 4 - H332</p>
<p><b>ISOPHORONEDIAMINE</b> <span style="float: right;"><b>10-30%</b></span></p> <p>CAS number: 2855-13-2                      EC number: 220-666-8                      REACH registration number: 01-2119514687-32-0000</p>
<p><b>Classification</b></p> <p>Acute Tox. 4 - H302 Acute Tox. 4 - H312 Skin Corr. 1B - H314 Eye Dam. 1 - H318 Skin Sens. 1 - H317 Aquatic Chronic 3 - H412</p>
<p><b>TRIETHYLENETETRAMINE</b> <span style="float: right;"><b>1-5%</b></span></p> <p>CAS number: 112-24-3                      EC number: 203-950-6</p>
<p><b>Classification</b></p> <p>Acute Tox. 4 - H312 Skin Corr. 1B - H314 Eye Dam. 1 - H318 Skin Sens. 1 - H317 Aquatic Chronic 3 - H412</p>

## ProTect ST and Protect STC curing agent

<b>XYLENE</b>		<b>1-5%</b>
CAS number: 1330-20-7	EC number: 215-535-7	REACH registration number: 01-2119488216-32-0000
<b>Classification</b>		
Flam. Liq. 3 - H226		
Acute Tox. 4 - H312		
Acute Tox. 4 - H332		
Skin Irrit. 2 - H315		
Asp. Tox. 1 - H304		
<b>ETHYLBENZENE</b>		<b>&lt;1%</b>
CAS number: 100-41-4	EC number: 202-849-4	REACH registration number: 01-2119489370-35-0000
<b>Classification</b>		
Flam. Liq. 2 - H225		
Acute Tox. 4 - H332		
STOT RE 2 - H373		
Asp. Tox. 1 - H304		

The full text for all hazard statements is displayed in Section 16.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

<b>Inhalation</b>	Move affected person to fresh air at once. Rinse nose and mouth with water. Never give anything by mouth to an unconscious person. Do not induce vomiting. Keep affected person warm and at rest. Get medical attention immediately.
<b>Ingestion</b>	Do not induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth thoroughly with water. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention immediately.
<b>Skin contact</b>	Remove affected person from source of contamination. Rinse immediately with plenty of water. Get medical attention promptly if symptoms occur after washing.
<b>Eye contact</b>	Remove any contact lenses and open eyelids wide apart. Rinse immediately with plenty of water. Continue to rinse for at least 15 minutes and get medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

**General information** No data available on the mixture itself.

#### 4.3. Indication of any immediate medical attention and special treatment needed

**Notes for the doctor** Treat symptomatically.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

**Suitable extinguishing media** Extinguish with the following media: Alcohol-resistant foam. Carbon dioxide (CO<sub>2</sub>). Dry chemicals, sand, dolomite etc. Do not use water, if avoidable.

#### 5.2. Special hazards arising from the substance or mixture

**Specific hazards** The product is flammable. Heating may generate flammable vapours.

## ProTect ST and Protect STC curing agent

**Hazardous combustion products** Thermal decomposition or combustion products may include the following substances: Toxic gases or vapours.

### 5.3. Advice for firefighters

**Protective actions during firefighting** Control run-off water by containing and keeping it out of sewers and watercourses.

**Special protective equipment for firefighters** Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions** Wear protective clothing as described in Section 8 of this safety data sheet.

**For non-emergency personnel** Keep unnecessary and unprotected personnel away from the area.

### 6.2. Environmental precautions

**Environmental precautions** Avoid discharge into drains or watercourses or onto the ground.

### 6.3. Methods and material for containment and cleaning up

**Methods for cleaning up** Keep combustible materials away from spillage. Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Stop leak if possible without risk. Absorb in vermiculite, dry sand or earth and place into containers. Avoid contamination of ponds or watercourses with washing down water.

### 6.4. Reference to other sections

**Reference to other sections** For personal protection, see Section 8. For waste disposal, see Section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

**Usage precautions** Keep away from heat, sparks and open flame. Do not wear contact lenses. Avoid spilling. Avoid contact with skin and eyes. Eye wash facilities and emergency shower must be available when handling this product. During application and drying, solvent vapours will be emitted.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage precautions** Store in tightly-closed, original container in a dry, cool and well-ventilated place. Store under well-ventilated conditions at a temperature below 25°C.

**Storage class** Corrosive storage.

### 7.3. Specific end use(s)

**Specific end use(s)** The identified uses for this product are detailed in Section 1.2.

## SECTION 8: Exposure controls/Personal protection

### 8.1. Control parameters

#### Occupational exposure limits

#### **XYLENE**

Long-term exposure limit (8-hour TWA): WEL 50 ppm(Sk) 220 mg/m<sup>3</sup>(Sk)

Short-term exposure limit (15-minute): WEL 100 ppm(Sk) 441 mg/m<sup>3</sup>(Sk)

Occupational Exposure Limits (Ireland):

Long-term exposure limit (8-hour TWA): NAOSH (Ireland) OELV 8 hours; 50 ppm 221 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): NAOSH (Ireland) OELV-15 min 100 ppm 442 mg/m<sup>3</sup>

## ProTect ST and Protect STC curing agent

### ETHYLBENZENE

Long-term exposure limit (8-hour TWA): WEL 100 ppm 441 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 125 ppm 552 mg/m<sup>3</sup>

Sk

Occupational Exposure Limits (Ireland):

Long-term exposure limit (8-hour TWA): NAOSH (Ireland) OELV 8 hours; 100 ppm 442 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): NAOSH (Ireland) OELV-15 min 200 ppm 884 mg/m<sup>3</sup>

WEL = Workplace Exposure Limit

Sk = Can be absorbed through the skin.

### 8.2. Exposure controls

#### Protective equipment



#### Appropriate engineering controls

Provide adequate general and local exhaust ventilation.

#### Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles. Personal protective equipment for eye and face protection should comply with European Standard EN166.

#### Hand protection

Wear protective gloves. To protect hands from chemicals, gloves should comply with European Standard EN374. Gloves made from the following material may provide suitable chemical protection: Nitrile rubber. Viton rubber (fluoro rubber). Polyvinylidene chloride/polyethylene (PVDC/PE). The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. Glove thickness is not necessarily a good measure of glove resistance as the permeation rate will depend on the exact glove composition. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected.

#### Other skin and body protection

Wear appropriate clothing to prevent skin contamination. Provide eyewash station.

#### Hygiene measures

Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly with soap and water if skin becomes contaminated. Promptly remove any clothing that becomes wet or contaminated.

#### Respiratory protection

No specific recommendations. Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Appearance	Viscous liquid.
Colour	Amber.
Odour	Characteristic.
pH	Not applicable.
Initial boiling point and range	137°C
Flash point	25°C Closed cup.

## ProTect ST and Protect STC curing agent

<b>Upper/lower flammability or explosive limits</b>	Lower flammable/explosive limit: 1.1% Upper flammable/explosive limit: 7%
<b>Vapour pressure</b>	Not available.
<b>Relative density</b>	0.97 - 1.01
<b>Solubility(ies)</b>	Immiscible with water.
<b>Partition coefficient</b>	Not available.
<b>Viscosity</b>	Kinematic viscosity > 20.5 mm <sup>2</sup> /s.
<b>9.2. Other information</b>	
<b>Other information</b>	No additional information
<b>Volatile organic compound</b>	This product contains a maximum VOC content of 29 g/l.

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

**Reactivity** See the other subsections of this section for further details.

#### 10.2. Chemical stability

**Stability** Stable at normal ambient temperatures.

#### 10.3. Possibility of hazardous reactions

**Possibility of hazardous reactions** Will not polymerise.

#### 10.4. Conditions to avoid

**Conditions to avoid** Avoid heat, flames and other sources of ignition.

#### 10.5. Incompatible materials

**Materials to avoid** Avoid contact with the following materials: Acids. Oxidising agents.

#### 10.6. Hazardous decomposition products

**Hazardous decomposition products** Ammonia or amines.

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

##### Acute toxicity - oral

**ATE oral (mg/kg)** 963.39

##### Acute toxicity - dermal

**ATE dermal (mg/kg)** 6,451.61

##### Acute toxicity - inhalation

**ATE inhalation (gases ppm)** 10,416.67

**ATE inhalation (vapours mg/l)** 25.46

**ATE inhalation (dusts/mists mg/l)** 3.47

**Inhalation** Harmful by inhalation. May cause damage to mucous membranes in nose, throat, lungs and bronchial system.

## ProTect ST and Protect STC curing agent

<b>Ingestion</b>	Causes burns. May cause chemical burns in mouth and throat. May cause stomach pain or vomiting.
<b>Skin contact</b>	Causes burns. Harmful in contact with skin. May cause sensitisation by skin contact. May cause allergic contact eczema. Product has a defatting effect on skin.
<b>Eye contact</b>	Severe irritation, burning and tearing. Causes burns.

### SECTION 12: Ecological information

**Ecotoxicity** The product contains a substance which may cause long-term adverse effects in the aquatic environment.

#### 12.1. Toxicity

**Toxicity** No data on the mixture itself.

#### 12.2. Persistence and degradability

**Persistence and degradability** No data available.

#### 12.3. Bioaccumulative potential

**Bioaccumulative potential** No data available on bioaccumulation.

**Partition coefficient** Not available.

#### 12.4. Mobility in soil

**Mobility** No data available.

#### 12.5. Results of PBT and vPvB assessment

**Results of PBT and vPvB assessment** This product does not contain any substances classified as PBT or vPvB.

#### 12.6. Other adverse effects

**Other adverse effects** None known.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

**General information** The generation of waste should be minimised or avoided wherever possible. Waste should be treated as controlled waste.

**Disposal methods** Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

### SECTION 14: Transport information

#### 14.1. UN number

**UN No. (ADR/RID)** 3066

**UN No. (IMDG)** 3066

**UN No. (ICAO)** 3066

**UN No. (ADN)** 3066

#### 14.2. UN proper shipping name

**Proper shipping name (ADR/RID)** PAINT RELATED MATERIAL

**Proper shipping name (IMDG)** PAINT RELATED MATERIAL

## ProTect ST and Protect STC curing agent

Proper shipping name (ICAO) PAINT RELATED MATERIAL

Proper shipping name (ADN) PAINT RELATED MATERIAL

### 14.3. Transport hazard class(es)

ADR/RID class	8
ADR/RID classification code	C9
ADR/RID label	8
IMDG class	8
ICAO class/division	8
ADN class	8

### Transport labels



### 14.4. Packing group

ADR/RID packing group	III
IMDG packing group	III
ICAO packing group	III
ADN packing group	III

### 14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

### 14.6. Special precautions for user

EmS	F-A, S-B
ADR transport category	3
Emergency Action Code	2X
Hazard Identification Number (ADR/RID)	80
Tunnel restriction code	(E)

### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended). Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).
----------------	--

## ProTect ST and Protect STC curing agent

**Guidance** Workplace Exposure Limits EH40.

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

### SECTION 16: Other information

**Abbreviations and acronyms used in the safety data sheet**

- WEL: Workplace Exposure Limit.
- ATE: Acute Toxicity Estimate.
- CAS: Chemical Abstracts Service.
- DMEL: Derived Minimal Effect Level.
- DNEL: Derived No Effect Level.
- PNEC: Predicted No Effect Concentration.
- PBT: Persistent, Bioaccumulative and Toxic substance.
- vPvB: Very Persistent and Very Bioaccumulative.

**Revision date** 14/08/2018

**Revision** 5

**Supersedes date** 15/02/2018

**SDS number** 19259

**Hazard statements in full**

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H332 Harmful if inhaled.
- H412 Harmful to aquatic life with long lasting effects.

The information in this SDS is based on the present state of our knowledge and meets the requirements of EU and national laws. The user's working conditions however, are beyond our knowledge and control. The product is not to be used for purposes other than those specified under section 1 without a written permission. It remains the responsibility of the user to ensure that the necessary steps are taken to meet the laws and regulations. Handling of the product may only be done by people above 18 years of age, who are satisfactorily informed of how to do the work, the hazardous properties and necessary safety precautions. The information given in this SDS is to describe the product only in terms of health and safety requirements and should not, therefore, be construed as guaranteeing specific properties.